



N.I.S. roofing felt adhesive CR50

The CR50 is an N.I.S. Adhesive. This product is used in cold processes to stick N.I.S. roofing papers, felt papers and asphalt paper. Its composition gives it a very strong adhesion on all types of surfaces without altering the composition of bonded materials. Its semi-liquid consistency is ideal for sticking asphalt shingles, protecting them from breakage caused by wind.



Advantages

Easy application with a paint brush
Excellent adhesion on any types of surface

Functions

Stick

Building components

Roofing

Surfaces

N.I.S. paper
Asphalt paper
Asphalt shingle
Felt paper

Application tools

Paint brush
Brush
Roller
Squeegee

Application temperature

10°C and more preferably. The product will be thicker when the temperature decreases.

Service temperature

-40°C to 85°C

Covering rate

0,44 m²/L
18 ft²/gallon

Standard

CAN/ONGC 37.4-M89

Colors

Black

% solid

65-75%

Surface preparation

Surfaces must be clean and free of dust, dirt or other contaminants. Repair the surfaces with plastic cement from Condor.



Application

Do not apply if rain is expected. During colder periods, keep the product in a temperate place to facilitate its application. Stir well before application. Apply the product in an even and thin layer. Close the container after each use.

Drying

Allow about 4h for surface drying and about 48h for complete drying. The drying time depends on the application method, the ambient temperature, the surface and the thickness applied.

Cleaning

Mineral spirits

Storage

The product may be kept in its original sealed container up to 12 months after the date of purchase by the user.

Format

3,78L / 18,9L

Restriction / Caution

Avoid contact with polystyrene foam insulation boards. Do not apply on wet surfaces. Keep out of the reach of children. If the product is applied near a ventilation or air conditioning unit, take the necessary precautions to prevent infiltration of solvent odours toward the inside. Keep open container or freshly applied product away from open flames, sparks or other sources of heat. For outdoor use only.

Warranty

5 years limited warranty when installed and / or applied as recommended by the manufacturer. We will replace the product with a manufacturing defect. Under no circumstances will the manufacturer be liable for any amount exceeding the purchase price of the product used. The consumer must ensure that this product is suitable for the intended use. Because of atmospheric conditions, applicator competence and surface conditions being independent of the manufacturer's control, we limit our liability for one year following the date of purchase, with proof of purchase, to replacement of defective material only in its original hermetic container. Port paid factory (FAB factory).



2645-B boul. Terra-Jet. Saint-Cyrille-de-Wendover (Qc) J1Z 1B3



819 474-6661



819 474-6681



www.condor.pro

DANGER



Flammable liquid and vapour.
May be fatal if swallowed and enters airways.
Suspected of causing cancer.
Causes damage to organs through prolonged or repeated exposure.

PRECAUTIONARY: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not breathe dust/ fumes/ gas/ mist/ vapours/ spray. Wash exposed and/or contaminated area thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/ protective clothing/ eye protection/ face protection.

IF SWALLOWED: Do NOT induce vomiting. Immediately call a POISON CENTER or a doctor. **IF EXPOSED:** Call a POISON CENTER or doctor/ physician. Get medical advice/ attention if you feel unwell. **IN CASE OF FIRE:** Use water fog, foam, dry chemical or carbon dioxide. Do not use straight of water. Store in a well ventilated place. Keep cool. Store locked up. Dispose of contents/ container by a local waste disposal company according to regional regulations.