



## Black Sealflex

### Annual black rustproofing

The rustproofing Sealflex Black is a product composed of corrosion inhibitors, wax, virgin oil and bitumen. It prevents rust formation on metal surfaces that are exposed to moisture, water or calcium. An annual application extends the life of your vehicle body. Being black, it becomes the ideal product for non-visible surfaces of the vehicle whether new or used, since it remains flexible and never completely dry. It doesn't trap moisture. This product has a gelatinous consistency which allows the product to adhere to the surface and to be easily dispersed in areas where water may collect. It is formulated to not leak. Its fruity odor makes it pleasant to use for applicators and the customers. It provides effective protection up to 2-3 years on coated parts that are not directly exposed to bad weather.



#### Advantages

- Made of virgin raw materials, without any contaminant
- Black finish
- Doesn't leak
- Fruity odor
- Doesn't damage paint or rubber trimmings
- Won't crack and stay flexible

#### Function

Protection against rust formation

#### Surface

- New or used metal
- Parts exposed directly to the weather:
- Rocker panels
- Fender wheels
- Wheel arch
- Underbody
- Frame

#### Service temperature

Max 85°C

#### Covering rate

2m<sup>2</sup>/L layer of 1/32 in

#### % solid

70-80%

#### Application fields

- Automobile
- Truck
- Industrial Application
- Agricultural Application

#### Color

Black gel

#### Application temperature

10°C and more

#### Application tools

Spray gun, paint brush

#### Cleaning

Mineral spirits



### Application

Ideally, keep the product in a temperate place. Shake well by tumbling or rolling on the ground before application. Following cleaning and thorough drying of the vehicle, apply the product in a thin layer at least 5 mils thick using a spray or brush. Use the necessary safety precautions for personal protection and cleanliness of the place of application.

### Drying

Allow about 5 hours for surface drying. The drying time depends on the application method, the ambient temperature and the surface.

### Storage

The product should be stored away from the sun to prevent premature oxidation of the product. It can be kept in its original sealed container until 12 months after the date of purchase by the user.

### Format

4L / 18,9L / 58L / 205L

### Restriction / Caution

Avoid using this product where the smell of solvents may affect food or other products that may be affected. Never apply to the inside of polymer panel, or electrical components or on fiberglass that has not been pre-coated with a factory primer.

### Warranty

The customer must ensure that this product is suitable for the intended purpose. Atmospheric conditions, applicator's skills and surface conditions being beyond the manufacturer's control, we limit our liability for one year following the date of purchase, with proof of purchase, to replacement of defective material only in its original hermetic container. Port paid plant (FOB plant).



2645-B, boul. Terra-Jet, Saint-Cyrille-de-Wendover (Qc) J1Z 1B3



819 474-6661



819 474-6681



[www.condor.pro](http://www.condor.pro)

## DANGER



Flammable liquid and vapour.

May be fatal if swallowed and enters airways. Suspected of causing cancer. Causes damage to organs through prolonged or repeated exposure.

**PRECAUTIONARY:** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not breathe dust/ fumes/ gas/ mist/ vapours/ spray. Wash exposed and/or contaminated area thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/ protective clothing/ eye protection/ face protection.

**IF SWALLOWED:** Do NOT induce vomiting. Immediately call a POISON CENTER or a doctor. **IF EXPOSED:** Call a POISON CENTER or doctor/physician. Get medical advice/attention if you feel unwell. **IN CASE OF FIRE:** Use water fog, foam, dry chemical or carbon dioxide. Do not use straight of water. Store in a well ventilated place. Keep cool. Store locked up. Dispose of contents/container by a local waste disposal company according to regional regulations.