



Primer CR70

The CR70 is an excellent primer. This product acts as a prime layer on roofs and foundations with a porous, dry or crumbly surface, which gives better adhesion. It also serves as a primer for concrete, masonry and other similar surfaces.



Advantages

- Provides a better grip
- Applicable on several types of materials

Functions

Primer

Building components

- Roofing
- Foundation

Surfaces

- Concrete
- Masonry
- Asphalt shingle
- Wood
- Metal

Application tools

- Roller
- Paint brush
- Spray gun

Application temperature

All temperature

Service temperature

-40°C to 85°C

Covering rate

3 m²/L
120 ft²/gallon

Standard

CAN/ONGC 37-GP-9MA

Colors

Black

% solid

55-60%

Surface preparation

Surfaces must be clean and free of dust, dirt or other contaminants. Surface repairs must first be done with plastic cement from Condor.



Application

Do not apply if rain is expected. During colder periods, keep the product in a temperate place to facilitate its application. Stir well before application. Apply the product in an even and thin layer. The primer must be completely dry before applying any other coating. Close the container after each use.

Drying

Allow about 1h for surface drying and about 8-24h for complete drying. The drying time depends on the application method, the ambient temperature, the surface and the thickness applied.

Cleaning

Mineral spirits

Storage

The product may be kept in its original sealed container up to 12 months after the date of purchase by the user.

Format

18,9L

Restriction / Caution

Do not apply on coal tar pitch roof (coal dust). Do not apply on wet surfaces. Keep out of the reach of children. If the product is applied near a ventilation or air conditioning unit, take the necessary precautions to prevent infiltration of solvent odours toward the inside. Keep open container or freshly applied product away from open flames, sparks or other sources of heat. For outdoor use only.

Warranty

5 years limited warranty when installed and / or applied as recommended by the manufacturer. We will replace the product with a manufacturing defect. Under no circumstances will the manufacturer be liable for any amount exceeding the purchase price of the product used. The consumer must ensure that this product is suitable for the intended use. Because of atmospheric conditions, applicator competence and surface conditions being independent of the manufacturer's control, we limit our liability for one year following the date of purchase, with proof of purchase, to replacement of defective material only in its original hermetic container. Port paid factory (FAB factory).

DANGER



Flammable liquid and vapour.

May be fatal if swallowed and enters airways. May cause cancer. Causes damage to organs through prolonged or repeated exposure.

PRECAUTIONARY: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not breathe dust/ fumes/ gas/ mist/ vapours/ spray. Wash exposed and/or contaminated area thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/ protective clothing/ eye protection/ face protection.

IF SWALLOWED: Do NOT induce vomiting. Immediately call a POISON CENTER or a doctor. If exposed: Call a POISON CENTER or doctor/ physician. Get medical advice/ attention if you feel unwell.

IN CASE OF FIRE: Use water fog, foam, dry chemical or carbon dioxide. Do not use straight of water. Store in a well ventilated place. Keep cool. Store locked up. Dispose of contents/ container by a local waste disposal company according to regional regulations.



2645-B, boul. Terra-Jet, Saint-Cyrille-de-Wendover (Qc) J1Z 1B3



819 474-6661



819 474-6681



www.condor.pro