



Sealflex elastomeric Plastic cement

See product code in the colors section

Colored plastic cement is used to effectively repair cracks in concrete, masonry, wood, gutters, asphalt shingles, metal roofs and roofs of recreational vehicles. Low VOC, it can also be used to stick asphalt shingles or caulk and seal chimney, vent and other flashings. It is ideal for making repairs before applying Sealflex Elastomeric Roof Coating. It is even possible to paint the product. This product is available in 8 colors: green, grey, brown, concrete grey, black, white, brick red and beige.



Advantages

- 100% acrylic and odourless
- High flexibility
- Seals perfectly the cracks
- Resists cracking and UV
- Indoor and outdoor use
- Several colors available

Functions

- Seal
- Stick

Building components

- Roofing
- Foundation

Surfaces

- Concrete
- Masonry
- Wood
- Gutters
- Asphalt shingles
- Metal
- RV roof membrane
- EDPM and TPO membrane

Application tools

- Putty knife
- Trowel
- Caulking gun

Application temperature

10°C and more

Service temperature

-40°C to 90°C

Covering rate

- 0,14 m²/kg applied 6 mm thick
- 0,68 pi²/lbs applied 1/4" thick

Standard



Colors

Green (CR-311) / grey (CR-312) / brown (CR-313) / concrete grey (CR-314) / black (CR-315) / white (CR-316) / brick red (CR-317) and beige (CR-319).

% solid

75-80%

Surface preparation

Surfaces must be clean and free of dust, dirt or other contaminants. Clean the surface with a universal degreaser except asphalt shingles. Brush and rinse thoroughly to remove all traces of soap. Sand smooth surfaces for better adhesion. Using a high pressure machine may be useful in some cases. Allow a drying time before applying the product.

Application

Do not apply if rain is expected. Try the product on a small surface to validate if the product is suitable. At the time of application and during the complete drying, the temperature should be above 10°C. Avoid application in direct sunlight or on a very hot surface. Repair cracks with a maximum width of 0.5" by 0.5" deep. The surface must be repaired to allow the flow of water. Allow to dry and harden by protecting the surface against the elements. Close the container after each use.

Drying

Allow about 20 minutes for surface drying and 24-48h for complete drying. The drying time depends on the application method, the ambient temperature, the surface and the thickness applied.

Cleaning

Water

Storage

Store this product away from frost. The product may be kept in its original sealed container up to 12 months after the date of purchase by the user.

Format

300ml / 1kg

Restriction / Caution



Warranty

5 years limited warranty when installed and / or applied as recommended by the manufacturer. We will replace the product with a manufacturing defect. Under no circumstances will the manufacturer be liable for any amount exceeding the purchase price of the product used. The consumer must ensure that this product is suitable for the intended use. Because of atmospheric conditions, applicator competence and surface conditions being independent of the manufacturer's control, we limit our liability for one year following the date of purchase, with proof of purchase, to replacement of defective material only in its original hermetic container. Port paid factory (FAB factory).

DANGER



May cause cancer.

Causes damage to organs through prolonged or repeated exposure.

PRECAUTIONARY: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust/ fumes/ gas/ mist/ vapours/ spray. Wash exposed and/or contaminated area thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/ protective clothing/ eye protection/ face protection.

IF EXPOSED: Call a POISON CENTER or doctor/physician. Get medical advice/ attention if you feel unwell. Store locked up. Dispose of contents/ container by a local waste disposal company according to regional regulations.



2645-B, boul. Terra-Jet, Saint-Cyrille-de-Wendover (Qc) J1Z 1B3



819 474-6661



819 474-6681



www.condor.pro